PORTAL

AL LIBRARY

Search Results

01/15/2002

Search Results for: [(compiler-controlled <near> bypass*)]
Found 4 of **87,654 searched.**   -> Rerun within the Portal

Search within Results

Go   > Advanced Search

> Search Help/Tips

Sort by: Title   Publication   Publication Date   Score   .☑ Binder

Results 1 - 4 of 4   short listing

1   Optimizing communication in HPF programs on fine-grain distributed shared memory   37%
Satish Chandra , James R. Larus
ACM SIGPLAN Notices , Proceedings of the sixth ACM SIGPLAN symposium on Principles & practice of parallel programming June 1997
Volume 32 Issue 7

2   An evaluation of bottom-up and top-down thread generation techniques   3%
A. P. W. Böhm , W. A. Najjar , B. Shankar , L. Roh
Proceedings of the 26th annual international symposium on Microarchitecture   December 1993

3   Lx   2%
Paolo Faraboschi , Geoffrey Brown , Joseph A. Fisher , Giuseppe Desoli , Fred Homewood
ACM SIGARCH Computer Architecture News , Proceedings of the 27th annual international symposium on Computer architecture May 2000
Volume 28 Issue 2
Lx is a scalable and customizable VLIW processor technology platform designed by Hewlett-Packard and STMicroelectronics that allows variations in instruction issue width, the number and capabilities of structures and the processor instruction set. For Lx we developed the architecture and software from the beginning to support both scalability (variable numbers of identical processing resources) and customizability (special purpose resources).   In this paper we consider the followi ...

4   Dynamic management of scratch-pad memory space   0%
M. Kandemir , J. Ramanujam , J. Irwin , N. Vijaykrishnan , I. Kadayif , A. Parikh
Proceedings of the 38th Conference on Design Automation Conference   June 2001
Optimizations aimed at improving the efficiency of on-chip memories are extremely important. We propose a compiler-controlled dynamic on-chip scratch-pad memory (SPM) management framework that uses both loop and data transformations. Experimental results obtained using a generic cost model indicate significant reductions in data transfer activity between SPM and off-chip memory.

Results 1 - 4 of 4   short listing

PORTAL
THE LIBRARY

Search Results

Search Results for: [(compiler-controlled <near> bypass*)]
Found 4 of 87,654 searched.   -> Rerun within the Portal

Search within Results

[   ] **GO**   > Advanced Search

> Search Help/Tips

Sort by: Title   Publication   Publication Date   Score   . **Binder**

Results 1 - 4 of 4   short listing

1   Optimizing communication in HPF programs on fine-grain distributed shared memory   37%
Satish Chandra , James R. Larus
ACM SIGPLAN Notices , Proceedings of the sixth ACM SIGPLAN symposium on Principles & practice of parallel programming June 1997
Volume 32 Issue 7

2   An evaluation of bottom-up and top-down thread generation techniques   3%
A. P. W. Böhm , W. A. Najjar , B. Shankar , L. Roh
Proceedings of the 26th annual international symposium on Microarchitecture   December 1993

3   Lx   2%
Paolo Faraboschi , Geoffrey Brown , Joseph A. Fisher , Giuseppe Desoli , Fred Homewood
ACM SIGARCH Computer Architecture News , Proceedings of the 27th annual international symposium on Computer architecture May 2000
Volume 28 Issue 2
   Lx is a scalable and customizable VLIW processor technology platform designed by Hewlett-Packard and STMicroelectronics that allows variations in instruction issue width, the number and capabilities of structures and the processor instruction set. For Lx we developed the architecture and software from the beginning to support both scalability (variable numbers of identical processing resources) and customizability (special purpose resources).   In this paper we consider the followi ...

4   Dynamic management of scratch-pad memory space   0%
M. Kandemir , J. Ramanujam , J. Irwin , N. Vijaykrishnan , I. Kadayif , A. Parikh
Proceedings of the 38th Conference on Design Automation Conference   June 2001
   Optimizations aimed at improving the efficiency of on-chip memories are extremely important. We propose a compiler-controlled dynamic on-chip scratch-pad memory (SPM) management framework that uses both loop and data transformations. Experimental results obtained using a generic cost model indicate significant reductions in data transfer activity between SPM and off-chip memory.

Results 1 - 4 of 4   short listing